



Technologie blad

Diver-SDI – AS379

Behuizing

Afmetingen (L × B × H)	65 mm × 50 mm × 35 mm
Gewicht	~82 g
Materiaal	ABS
Beschermingsklasse	IP65

Verbindingen

Diver kabel	M12 connector (verbind met AS2xxx kabel) Lengte: 0.5 tot 500 meter Kabelwartel PG-7
SDI-12 Compatibele Diver modellen	Mini-Diver (DI5xx), Micro-Diver (DI6xx), Cera-Diver (DI7xx), CTD-Diver (DI27x), TD-Diver (DI8xx)

Vermogensverbruik

Externe voedingsspanning	8 tot 16 V
Stand-by stroom	50 µA
Maximale stroom	10 mA

SDI-12 bus

Compatibiliteit	SDI-12 V1.4
Communicatie	1200 bps, 7 bits, even pariteit, 1 stop bit
Multi-drop	ja, maximaal 8
Adres	programmeerbaar: '0' to '9', 'A' to 'Z' and 'a' to 'z'

Druk

Bereik	400 tot 1100 cmH ₂ O
Nauwkeurigheid*	±2.0 cmH ₂ O
Resolutie	0.06 cmH ₂ O

Temperatuur

Bereik	-20 tot 80 °C
Gekalibreerd bereik	0 tot 50 °C
Nauwkeurigheid*	±1 °C
Resolutie	0.2 °C

* maximum

