



Technologie blad

Diver-MOD – AS339

Behuizing

Afmetingen (L × B × H)	65 mm × 50 mm × 35 mm
Gewicht	~82 g
Materiaal	ABS
Beschermingsklasse	IP65

Verbindingen

Diver kabel	M12 connector (verbind met AS2xxx kabel) Lengte: 0.5 tot 500 meter
SDI-12	Kabelwartel PG-7
Compatibele Diver modellen	Mini-Diver (DI5xx), Micro-Diver (DI6xx), Cera-Diver (DI7xx), CTD-Diver (DI27x), TD-Diver (DI8xx)

Vermogensverbruik

Externe voedingsspanning	5 VDC
Stand-by stroom	2 mA
Maximale stroom	50 mA

Modbus

Communicatie	RS485 half-duplex, single pair, 300 bps tot 115,200 bps
Multi-drop	ja, maximaal 8 apparaten per communicatielink
Adres	programmeerbaar: 1 tot 247

Druk

Bereik	400 tot 1100 cmH ₂ O
Nauwkeurigheid*	±2.0 cmH ₂ O
Resolutie	0.06 cmH ₂ O

Temperatuur

Bereik	-20 tot 80 °C
Gekalibreerd bereik	0 tot 50 °C
Nauwkeurigheid*	±1 °C
Resolutie	0.2 °C

* maximum

